

STREETLIGHT NOTES:

- 1. STREETLIGHTS SHALL BE INSTALLED AS PART OF THE ULTIMATE ROAD IMPROVEMENTS REQUIRED.
- 2. STREETLIGHTS SHALL BE INSTALLED AT LOTLINES WHENEVER PRACTICAL.
- 3. STREETLIGHTS SHALL BE PLACED ALTERNATELY ON EACH SIDE OF THE ROADWAY AND SHALL BE SPACED/PLACED AS FOLLOWS:
 - A). INTERSECTIONS OF TWO STREETS
 - B). "T" INTERSECTIONS
 - C). AT STREET KNUCKLES
 - D). AT CUL-DE-SACS
 - E). SPACING SHALL BE 200 FEET (61m) FOR LOCAL AND COLLECTOR STREETS AND 100 FEET (30.5m) FOR OTHERS.
- 4. A NON-GLARE RECTILINEAR LAMPHEAD SHALL BE USED UNLESS OTHERWISE DIRECTED BY THE CITY ENGINEER.
- 5. LAMPS SHALL BE HIGH PRESSURE SODIUM VAPOR (HPSV), 200 WATTS FOR ARTERIALS AND 100 WATT FOR OTHERS.

DRAWN BY: C.A.C. DESIGNED BY:	CITY OF PASO ROBLES ENGINEERING DIVISION	DRAWING NO.
DATE: 4/18/94 FILE NAME: PR-U-5 DWG	STREET LIGHT LOCATION DETAILS	U-5